

NOW AVAILABLE

NEW

JACKSON[®]
SAFETY

AIRMAX HM

AIR FED PAPR SYSTEM WITH HALF MASK

● REDUCED FLOW RATE
Field tested Airmax blower adapted for half mask use*

● NEW CUSTOM FLEXIBLE HOSE
FR hose cover available

● S/M, M/L
Available in small/medium and medium/large sizes

APPLICATIONS

- Can be used in construction environment with high Silica dust content.
- Fits under face shields and welding helmets; can be used with hard hats, earplugs, glasses and goggles.



CE
1024

EN 12942:1998+A2:2008
TM3 P R SL

Particle Protection

TM3

Airflow

120 lpm

Charging time

5 hrs

Operation time

9 hrs

Can be worn with backpack



Positive pressure air feed reduces worker fatigue

Unique blower/hose attachment that prevents other headtops being connected



Audible Filter Alarms to inform when filters need changing or low battery

Replacement filter available



Silicon material creates a softer more ergonomic feel on the users face



Compact design to ensure this can be used under most welding helmets and face shields

Extra layer of security:
Hose and half mask can not be separated due to additional 'neck-gripper'

*Note - cannot be used with DUO headtop

LEARN MORE



46311 Airmax HM PAPR System (Blower, belt, battery, battery charger, test tube, filter)

46313 Half mask with hose and hose connector, size S/M

46314 Half mask with hose and hose connector, size M/L

AVAILABLE SIZES

S/M

M/L

FACE FIT
REQUIRED

SureWerx[®]

Be Smart. Be Safe. Be Sure.[®]

EU Ordering E-mail eusales@surewerx.com

UK Ordering E-mail uksales@surewerx.com

www.surewerx.eu